



ⒶPower inlet (φ60) Breaker capacity (factory), 200V Class:200A (P400B, G450B:225A)/400V Class:100A (P400B, G450B:125A)

ⒷWater for hopper throat IN:Rc3/8 (Nomal water volume:5 to 10 ℓ/min.with Y-type strainer)

ⒸWater for hopper throat OUT:Rc3/8

※Overall machine height increases by approx.47mm with optional rubber pads attached.

射出装置名 (スクリュエー直径)	L	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L <sub>4</sub>	W <sub>1</sub>	W <sub>2</sub>	W <sub>3</sub>	【H <sub>1</sub> 】	【H <sub>2</sub> 】	【H <sub>3</sub> 】	【H <sub>4</sub> 】	
													φ
7H・7U	φ32	5727	1126	731	1494	-145	1107	475	632	120	505	625	1922
	φ36	5727	1209	814	1494	-62	1107	475	632	120	505	625	1922
	φ40	5783	1307	912	1514	56	1107	475	632	125	505	630	1927
	φ46	5956	1444	1049	1550	229	1107	475	632	125	570	695	1992
15H・15U	φ40	5915	1307	912	1646	188	1060	366	694	125	505	630	1927
	φ46	6088	1444	1049	1682	361	1060	366	694	125	570	695	1992
	φ50	6158	1530	1135	1666	431	1060	366	694	130	570	700	1997
20H	φ55	6378	1709	1314	1707	651	1060	366	694	155	570	725	2022
	φ50	6198.5	1530	1135	1706.5	471.5	1123	398	725	130	570	700	1997
	φ55	6372	1709	1314	1701	645	1123	398	725	155	570	725	2022
φ60	6544	1818	1423	1764	817	1123	398	725	165	645	810	2107	

Figures in 【 】 show dimensions with options.